



G3650

3U EnergySaving server chassis

- build in Intelligent EnergySaving function
- efficiently fan life time extendable
- build in removable front key-lock door with air filter
- HDD drive bay with anti-vibration function
- high grade aluminum rackmounting handles
- support 12"x13" eATX or smaller MB
- main construction sheet metal by 1.2mm~2.0mm
- high & clean grade Korean SECC (not cheap SGCC)
- easy swap removable 12cm fan brackets
- most Taiwan RPS durable fixed at inside & outside
- normal PS2 & most Taiwan RPS makers approved
- build in Sunon 120mmx25mm 2ball bearing fans
- bare noise @ 29dBA (fan noise against room noise)
- IPC China branded model global 3 years warranty

Storage capacity: 6 x 5.25" DVD and 2 x 3.5" HDD and 2 x 2.5" HDD bay

- * Intelligent EnergySaving device's default is all fans automatically activated if system temperature up to 38 degree-C
- * Intelligent EnergySaving device's default is 38 degree-C but individual fan can be adjusted between 30~60 degree-C
- * Intelligent EnergySaving device supported with four fan fail's indication and warning (stop warning by any button)
- * Intelligent EnergySaving device supported with Celsius or Fahrenheit Degree (convertible by C/F button)
- * Build in security butterfly key-lock front door with removable air filter
- * HDD drive bay with anti-vibration function
- * Build in high grade aluminum rackmounting handles
- * Build with high & clean grade Korean SECC sheet metal by 1.2mm~2.0mm thickness
- * Equipped two USB 2.0 ports
- * Build in two set of easy swap removable 12cm fan brackets inside of chassis
- * Cooling by two brand new Sunon EEC0251B1-000C-G99 120mmx25mm 2ball bearing intake fans
- * Room noise without fan activated is 41dBA, tested by 10cm distance to the running fan is 70dBA (including room noise)
- * Support standard eATX(12"x13") & eATX(12"x10.5") & ATX(12"x9.6") & Mini-ITX(6.7"x6.7") MB
- * Support PS2 power supply with 120mm~140mm fan version (max. psu depth: 200mm)
- * Or support PS2 Mini Redundant power supply by Zippy, Etasis, and Enermax (max. psu depth: 200mm)
- * Support 4 slot full high expansion cards (max. 342mm long)
- * Standard paint: black
- * IPC China branded server chassis model (with build-in fans) global 3 years warranty
- * Chassis dimension: 19" x 3U x 650mm (25.59" deep)
- * Package: NW 11.50 KGM, GW 13.60 KGM, 3.50 CUFT (carton size: 570x790x220mm)
- * Green Energy saving server patent pending areas: China, Taiwan, Thailand, Korea, Japan, USA, UK, EU, Russia
- * Patent and Law attorney agency: China GuanDong Kwo Hui Attorney at Law



Ordering Information:

Chassis model # & description: G3650 3U EnergySaving server chassis

Optional part# & description 1-0: Support PS2 psu with 120mm~140mm fan version (max. psu depth: 200mm)

Optional part# & description 1-1: Support & approved by Zippy MRT/MRW/MRG 185mm~200mm deep 300W~800W redundant power supply

Optional part# & description 1-2: Support & approved by Etasis EFRP-2462 190mm deep 460W redundant power supply

Optional part# & description 1-3: Support & approved by Enermax EMA series (460W/550W) 199mm deep redundant power supply

Optional part# & description 1-4: Support & approved by Enhance ENR0500 series (400W/500W/600W) 185mm deep redundant power supply

Optional part# & description 2-0: (NJ-600) 600mm 2-layer 3-travel universal slide rail (part# is 1 pair)

Optional part# & description 2-1: (1234U-RMK) 1234U rear mounting kit (part# is 1 pair)

Optional part# & description 3-0: (SUNON6025) Sunon 60mmx25mm 2ball fan (part# is 1pcs, can install 2pcs at rear)

Optional part# & description 4-0: (25-35-BK) 5.25" space to one 3.5" HDD or one 3.5" HDD space to two 2.5" HDD bracket

Optional part# & description 5-0: (2525TO3HDBK) two 5.25" drive space converted into three 3.5" HDD bracket

Optional part# & description 5-1: (3525TO5HDBK) three 5.25" drive space converted into five 3.5" HDD bracket

Optional part# & description 5-2: (SS-46TM) 1x5.25" to 4x2.5" SAS/SATA Hot-Swap Cage

Optional part# & description 5-3: (SS-86TM) 2x5.25" to 8x2.5" SAS/SATA Hot-Swap Cage

Optional part# & description 5-4: (S-36TM) 2x5.25" to 3x3.5" SAS/SATA Hot-Swap Cage

Optional part# & description 5-5: (S-36TL) 2x5.25" to 3x3.5" TrayLess SAS/SATA Hot-Swap Cage

Optional part# & description 5-6: (S-16TL) 1x5.25" to 1x3.5" TrayLess SAS/SATA Hot-Swap Cage

Latest updated on June 02, 2013

IPC China Corporation Copyright reserved©

Without official doc authorized, any commercial behaviors including design & photo are prohibited

中國工控
IPC CHINA
www.chinaipc.cc