

### R2380

2U Black MicroATX server chassis

- 01) build in removable front cover with air filter
- 02) HDD drive bay with anti-vibration function
- 03) compatible with 3.5" HDD or 2.5" HDD (option)
- 04) support 9.6"x9.6" MicroATX & 6.7"x6.7" Mini-ITX MB
- 05) main construction sheet metal by 1.2mm~2.0mm
- 06) build in Sunon 80mmx25mm two ball bearing fans
- 07) bare noise @ 25dBA (fan noise against room noise)
- 08) IPC China branded model global 3 years warranty



### Specification:

- \* Drive capacity:
  - two 5.25" DVD and two 3.5" HDD bay
- \* Build in removable front cover with air filter
- \* Equipped two USB 2.0 port
- \* HDD drive bay with anti-vibration function
- \* Major sheet metal by SGCC 1.2mm~2.0mm thickness
- \* Two Sunon EE80251B1-000C-G99 80mmx25mm intake fans behind the air filter of front bezel
- \* Room noise without fan activated is 40dBA, tested by 10cm distance to the running fan is 65dBA (including room noise)
- \* Support 9.6"x9.6" MicroATX and 6.7"x6.7" Mini-ITX MB
- \* Support PS2 power supply with 120mm~140mm fan version (max. psu depth: 140mm~180mm)
- \* If 140mm deep PS2 psu installed, max. 210mm deep 5.25" ODD device compatible
- \* If 180mm deep PS2 psu installed, max. 170mm deep 5.25" ODD device compatible
- \* Support 4 slot Low Profile expansion cards (max. 170mm deep if HDD installed, 330mm deep if HDD not installed)
- \* Standard paint: black
- \* IPC China branded server chassis model (with build-in fans) global 3 years warranty
- \* Chassis dimension: 19" x 2U x 380mm (14.96" deep)
- \* Accessory pack: M3 round head nickel screw x 8pcs, #6 round head nickel screw x 20pcs
- \* Package: NW 5.5 KGM, GW 7.5 KGM, 1.72 CUFT (56x51x17cm, single box packed)
- \* Patent and Law attorney agency: China GuanDong Kwo Hui Attorney at Law



### Ordering Information:

- Chassis model # & description: R2380 2U Black MicroATX server chassis
- Optional part# & description 1-0: PS2 power supply with 120mm~140mm fan version (max. psu depth: 140mm~180mm)
  - Optional part# & description 2-0: (NJ-600) 600mm 2-layer 3-travel universal slide rail (part# is 1 pair)
  - Optional part# & description 2-1: (1234U-RMK) 1234U rear mounting kit (part# is 1 pair)
  - Optional part# & description 3-0: (25-35-BK) 5.25" space to one 3.5" HDD or one 3.5" HDD space to two 2.5" HDD bracket
  - Optional part# & description 4-0: (2525TO3HDBK) two 5.25" drive space converted into three 3.5" HDD bracket
  - Optional part# & description 4-1: (SS-46TM) 1x5.25" to 4x2.5" SAS/SATA Hot-Swap Cage
  - Optional part# & description 4-2: (SS-86TM) 2x5.25" to 8x2.5" SAS/SATA Hot-Swap Cage
  - Optional part# & description 4-3: (S-36TM) 2x5.25" to 3x3.5" SAS/SATA Hot-Swap Cage
  - Optional part# & description 4-4: (S-36TL) 2x5.25" to 3x3.5" TrayLess SAS/SATA Hot-Swap Cage
  - Optional part# & description 4-5: (S-16TL) 1x5.25" to 1x3.5" TrayLess SAS/SATA Hot-Swap Cage



Updated on November 12, 2013