



R4450A

4U black eATX server chassis

- ① Sheet metal all by 1.2mm ~ 2.0mm thickness
- ① International standard with high grade SGCC metal
- ① Chassis depth 450mm but 342mm card compatible
- ① Meets eATX12"x13" MB or 14 slot PICMG backplane
- ① Equipped with dust-proof air filter at front bezel
- ① 12 short-medium-long hold down card clamps
- ① Compatible with PS2 or PS2 Mini-Redundant PSU
- ① bare noise @ 25dBA (fan noise against room noise)
- ① IPC China branded product global warranty 3 years

- * Drive bay housing: three 5.25" DVD bay and two 3.5" HDD bay (one of 3.5" can be FDD)
- * Two USB 2.0 ports at the front bezel (behind the security front door)
- * One PS2 keyboard connector at front bezel as industrial application
- * Build in one brand new 120mmx25mm intake fan behind the dustproof filter
- * Build in high grade aluminum rackmounting handles
- * Build with high & clean sheet metal by 1.2mm~2.0mm thickness
- * Room noise without fan activated is 46dBA, tested by 10cm distance to the running fan is 71dBA (including room noise)
- * Build in 12 short-medium-long hold down card clamps upward or downward adjustable
- * Compatible MB: standard EEB (12"x13")·CEB (12"x10.5")·ATX (12"x9.6")·MicroATX (9.6"x9.6")·Mini-ITX (6.7"x6.7")
- * Compatible with PS2 or PS2 Mini-Redundant power supply (maximum power depth at 200mm)
- * Compatible with 7 slot full height expansion cards (maximum up to 342mm long)
- * Equipped with 8 plug-in card guidances to hold full-size 342mm deep cards
- * Standard paint: black micro sand texture durable against scratch
- * IPC China branded product including build in fan(s) global warranty 3 years
- * Chassis dimension: 19" x 4U x 450mm (17.71" deep)
- * Package: NW 12.00 KG, GW 15.60 KG, 3.35 CUFT (60x54.5x29cm, single box packed)
- * IPC China brand Copyright reserved



Ordering Information:

Ordering Model Number and description: (R4450A) 4U black eATX server chassis

Ordering Model Number and description: (R4450A-W) 4U beige eATX server chassis

Optional part number and description1-0: Support PS2 power supply with 120mm~140mm fan version (max. psu depth: 200mm)

Optional part number and description1-1: Support & approved by Zippy MRT/MRW/MRG 185mm~200mm deep 300W~800W redundant power supply

Optional part number and description1-2: Support & approved by Etasis EFRP-2462 190mm deep 460W redundant power supply

Optional part number and description1-3: Support & approved by Enermax EMA series (460W/550W) 199mm deep redundant power supply

Optional part number and description1-4: Support & approved by Enhance ENR0500 series (400W/500W/600W) 185mm deep redundant power supply

Optional part number and description 2-0: (NJ-600) 600mm 2-layer 3-travel universal slide rail (part# is 1 pair)

Optional part number and description 2-1: (1234U-RMK) 1234U rear mounting kit (part# is 1 pair)

Optional part number and description 3-0: (SUNON6025) Sunon two-ball bearing 60mm x 25mm exhaust fan at ATX 7 slot rear panel (part# is 1pcs)

Optional part number and description 4-0: (R4450A-14S-RP) black 14 slot PICMG rear panel

Optional part number and description 4-1: (R4450A-14S-RP-W) beige 14 slot PICMG rear panel

Latest updated on October 22, 2012

IPC China Corporation Copyright reserved©

Without official doc authorized, any commercial behaviors including design & photo are prohibited

中國工控
IPC CHINA
www.chinaipc.cc