

G2380 2U MicroATX EnergySaving server chassis



SPECIFICATION

- * EnergySaving function 1: Default is all fans automatically activated if system temperature up to 38 degree-C
- * EnergySaving function 2: Default is 38 degree-C but individual fan can be adjusted between 30~60 degree-C
- * EnergySaving function 3: Four fan fail display and alert (stop warning by any button)
- * EnergySaving function 4: Device can be switched to Celsius or Fahrenheit Degree (push C/F button)
- * Drive space: Two 5.25" ODD & two 3.5" HDD
- * Drive space: or one 5.25" ODD & two 3.5" HDD & two 2.5" SSD
- * Drive space: or one 5.25" ODD & three 3.5" HDD
- * Aluminum alloy die casting handles, main sheet metal at 1.2mm~2.0mm SECC thickness mechanism
- * Standard with two USB 2.0 ports and LAN/HDD/Power LED at front bezel (two USB 3.0 as option)
- * Standard equipped with Removable dust filter at front bezel
- * Build in two brand new 80mmx25mm intake fans behind the front air filter (fan part# D80SM-12)
- * Compatible MB: MicroATX (9.6"x9.6"), Mini-ITX (6.7"x6.7")
- * 8cm or 12cm~14cm fan version standard PS2 PSU compatible (depth at 140mm~180mm)
- * If 140mm deep PS2 psu installed, max. 210mm deep 5.25" ODD device compatible
- * If 180mm deep PS2 psu installed, max. 170mm deep 5.25" ODD device compatible
- * If front fixed with 3.5" HDD, 4 slot low profile cards (max. depth at 170mm)
- * If front fixed without 3.5" HDD & bracket, 4 slot low profile cards (max. depth at 330mm)
- * Standard paint: scratch-resistant black textured at front side of chassis
- * IPC China chassis with all build-in electronics in global 3 years warranty
- * Chassis dimension: 19" x 2U x 380mm (14.96" deep)
- * Accessory: #6 round x28, #6 countersunk x4, M3 countersunk x8, M3 truss x7, Low Profile bracket x1
- * Package: NW 5 KGM, GW 6.5 KGM, 1.75 CUFT (carton size at 56.5x51.5x17cm)
- * Green EnergySaving Patent and Law attorney agency: China GuanDong Kwo Hui Attorney at Law



ORDERING INFORMATION

- Model#: G2380 2U MicroATX EnergySaving server chassis
- Option A-1 : NJ-600 600mm 2-layer 3-travel universal rail (cabinet internal depth at 575mm~1200mm compliant)
 - Option A-2 : NJ-2020-18 18-inch full extension slide rail (cabinet internal depth 456.7mm~810mm compliant)
 - Option A-3 : 1234U-RMK 1234U rear mounting kit
 - Option B : PS2 PSU 8cm or 12cm~14cm fan version standard PS2 PSU compatible (depth at 140mm~180mm)
 - Option C : 25-35-BK 1x5.25" to 1x3.5" bracket or 1x3.5" HDD space to 2x2.5" SSD bracket
 - Option D-1 : N-16TM 1x5.25" to 1x3.5" HotSwap Cage SATA/SAS 12G
 - Option D-2 : S-16TM 1x5.25" to 1x3.5" HotSwap Cage SATA/SAS 6G
 - Option D-3 : N-16TL 1x5.25" to 1x3.5" TrayLess HotSwap Cage SATA/SAS 12G
 - Option D-4 : S-16TL 1x5.25" to 1x3.5" TrayLess HotSwap Cage SATA/SAS 6G
 - Option D-5 : N-29SS15 1x5.25" to 2x2.5" HotSwap Cage SATA/SAS 12G
 - Option D-6 : N-67SS 1x5.25" to 6x2.5" HotSwap Cage SATA/SAS 12G
 - Option D-7 : SS-88TM 1x5.25" to 8x2.5" HotSwap Cage SATA/SAS 6G
 - Option D-8 : N-49NVMe 1x5.25" to 4x2.5" SSD Removable Cage U.2 NVMe 32G
 - Option D-9 : N-49SS-MS 1x5.25" to 4x2.5" HotSwap Cage SFF-8643 12G
 - Option D-10 : N-49SS 1x5.25" to 4x2.5" HotSwap Cage SATA/SAS 12G
 - Option D-11 : SS-46TM 1x5.25" to 4x2.5" HotSwap Cage SATA/SAS 6G
 - Option E-1 : SS-86TM 2x5.25" to 8x2.5" HotSwap Cage SATA/SAS 6G
 - Option E-2 : N-36TM 2x5.25" to 3x3.5" HotSwap Cage SATA/SAS 12G
 - Option E-3 : S-36TM 2x5.25" to 3x3.5" HotSwap Cage SATA/SAS 6G
 - Option E-4 : N-36TL 2x5.25" to 3x3.5" TrayLess HotSwap Cage SATA/SAS 12G
 - Option E-5 : S-36TL 2x5.25" to 3x3.5" TrayLess HotSwap Cage SATA/SAS 6G
 - Option F-1 : 1MSAS-4SATA-500MM SFF-8643 Mini-SAS (Host) to Four SATA (Device) cable
 - Option F-2 : SFF-8643-500MM SFF-8643 Mini-SAS HD (Host) to SFF-8643 Mini-SAS HD (Device) cable
 - Option F-3 : 4SATA-SFF-8643-500MM Four SATA (Host) to SFF-8643 Mini-SAS HD (Device) cable
 - Option F-4 : SFF-8643-4SATA-500MM SFF-8643 Mini-SAS HD (Host) to Four SATA (Device) cable
 - Option G-1 : 2U2011A-8080 2U Intel LGA2011 LGA2066 active CPU cooler Square
 - Option G-2 : 2U2011A-5694 2U Intel LGA2011 active CPU cooler Narrow
 - Option G-3 : 2U1150A 2U Intel LGA115x Xeon 1230 active CPU cooler
 - Option G-4 : 2U4094A-SP3 2U AMD EPYC LGA4094 active CPU cooler SP3
 - Option G-5 : 2U1331A-AM4 2U AMD LGA1331 active CPU cooler AM4
 - Option G-6 : 2U3647A-S82 2U Intel LGA3647 active CPU cooler Square
 - Option G-7 : 2U3647A-R82-1 2U Intel LGA3647 active CPU cooler Narrow



Latest updated on January 15, 2021