



## G2380D

### 2U EnergySaving server chassis

- 01) build in Intelligent EnergySaving function
- 02) efficiently fan life time extendable
- 03) build in security front door with removable air filter
- 04) compatible with 3.5" HDD or 2.5" HDD
- 05) high grade aluminum rackmounting handles
- 06) support 9.6"x9.6" MicroATX & 6.7"x6.7" Mini-ITX MB
- 07) main construction sheet metal by 1.0mm~2.0mm
- 08) **build in Sunon 60mmx25mm two ball bearing fans**
- 09) **bare noise @ 33dBA (fan noise against room noise)**
- 10) **IPC China branded model global 3 years warranty**

\* Drive capacity:

- two 5.25" DVD and two 3.5" HDD bay  
(or one 5.25" DVD and two 2.5" HDD and two 3.5" HDD bay)  
(or one 5.25" DVD and three 3.5" HDD bay)

- \* Intelligent EnergySaving device's default is all fans automatically activated if system temperature up to 38 degree-C
- \* Intelligent EnergySaving device's default is 38 degree-C but individual fan can be adjusted between 30~60 degree-C
- \* Intelligent EnergySaving device supported with four fan fail's indication and warning (stop warning by any button)
- \* Intelligent EnergySaving device supported with Celsius or Fahrenheit Degree (convertible by C/F button)
- \* Build in high grade butterfly keylock security front door with removable filter (90-degree open/close, trayless HDD compatible)
- \* Equipped two USB 2.0 port
- \* Build in high grade and durable aluminum rackmounting handles, all sheet metal by SECC 1.0mm~2.0mm thickness
- \* Two Sunon EB60251B1-000C-C99 60mmx25mm intake 2ball-bearing fans behind the air filter of front bezel
- \* Room noise without fan activated is 44dBA, tested by 10cm distance to the running fan is 77dBA (including room noise)
- \* Support 9.6"x9.6" MicroATX and 6.7"x6.7" Mini-ITX MB
- \* Support PS2 power supply with 80mm fan version (max. psu depth: 140mm~180mm)
- \* If 140mm deep PS2 psu installed, max. 210mm deep 5.25" ODD device compatible
- \* If 180mm deep PS2 psu installed, max. 170mm deep 5.25" ODD device compatible
- \* Support 4 slot Low Profile expansion cards (max. 170mm deep if HDD installed, 330mm deep if HDD not installed)
- \* Standard paint: black
- \* IPC China branded server chassis model (with build-in fans) global 3 years warranty
- \* Chassis dimension: 19" x 2U x 380mm (14.96" deep)
- \* Package: NW 5 KGM, GW 6.5 KGM, 1.75 CUFT (56.5x51.5x17cm, single box packed)
- \* Green Energy saving server patent pending areas: China, Taiwan, Thailand, Korea, Japan, USA, UK, EU, Russia
- \* Patent and Law attorney agency: China GuanDong Kwo Hui Attorney at Law

Ordering Information:

Chassismodel # & description: G2380D 2U EnergySaving server chassis

Optional part# & description 1-0: Support PS2 power supply with **80mm fan version** (max. psu depth: 140mm~180mm)

Optional part# & description 2-0: (NJ-600) 600mm 2-layer 3-travel universal slide rail (part# is 1 pair)

Optional part# & description 2-1: (1234U-RMK) 1234U rear mounting kit (part# is 1 pair)

Optional part# & description 3-0: (25-35-BK) 5.25" space to one 3.5" HDD or one 3.5" HDD space to two 2.5" HDD bracket

Optional part# & description 4-0: (2525TO3HDBK) two 5.25" drive space converted into three 3.5" HDD bracket

Optional part# & description 4-1: (SS-46TM) 1x5.25" to 4x2.5" SAS/SATA Hot-Swap Cage

Optional part# & description 4-2: (SS-86TM) 2x5.25" to 8x2.5" SAS/SATA Hot-Swap Cage

Optional part# & description 4-3: (S-36TM) 2x5.25" to 3x3.5" SAS/SATA Hot-Swap Cage

Optional part# & description 4-4: (S-36TL) 2x5.25" to 3x3.5" TrayLess SAS/SATA Hot-Swap Cage

Optional part# & description 4-5: (S-16TL) 1x5.25" to 1x3.5" TrayLess SAS/SATA Hot-Swap Cage



Latest updated on January 09, 2014

IPC China Corporation Copyright reserved©

Without official doc authorized, any commercial behaviors including design & photo are prohibited

中國工控  
IPC CHINA  
www.chinaipc.cc