

R4380 4U ATX rackmount server chassis



SPECIFICATION

- * Drive Space: Six 5.25" ODD bay & two 2.5" SSD/HDD bay (SSD at 7mm~15mm height allowed)
- * Removable front dust filter cover with captive hand screws
- * High strength aluminum alloy die casting handles ensure stability during rackmounting
- * The main sheet metal constructed by 1.2mm~2.0mm SECC thickness mechanism
- * Standard with two USB 2.0 ports and LAN/HDD/Power LED at front bezel (two USB 3.0 as option)
- * Standard with one brand new 80mmx25mm intake fan at front (fan part# D80SM-12)
- * Build-in two 80mmx25mm ABS screwless fan brackets at rear panel (fans are option)
- * 8cm or 12cm~14cm fan version standard PS2 PSU compatible (depth at 140mm~200mm)
- * Support SureStar R4S series 400W~500W PS2 Mini Redundant PS (depth 174mm)
- * Support Zippy MRT & MRW series 300W~600W PS2 Mini Redundant PS (depth 185mm)
- * Support SureStar R4B series 600W~800W PS2 Mini Redundant PS (depth 199mm)
- * Support Zippy MRG series 500W~800W PS2 Mini Redundant PS (depth 200mm)
- * Compatible motherboard: ATX(12"x9.6"), MicroATX(9.6"x9.6"), Mini-ITX(6.7"x6.7")
- * Support 7 slot full height expansion cards (max. depth at 340mm if no 5.25" device installed at front)
- * Standard paint: scratch-resistant black textured at front side of chassis
- * IPC China branded server chassis (with build-in fan) global 3 years warranty
- * Chassis dimension: 19" x 4U x 380mm (14.96" deep)
- * Accessory: #6 round x14, M3 truss x32, plastic MB stand-off x1, copper MB stand-off x2
- * Package: NW 7.3 KGM, GW 9.3 KGM, 2.78 CUFT (56x53x26.5cm, durable box packed)
- * Patent and Law attorney agency: China GuanDong Kwo Hui Attorney at Law



ORDERING INFORMATION

Model# : R4380 4U ATX rackmount server chassis

Option A-1 : PS2 PSU 8cm or 12cm~14cm fan version standard PS2 PSU compatible (depth at 140mm~200mm)

Option A-2 : PS2 RPS SureStar R4S series 400W/500W PS2 Mini Redundant PS (depth at 174mm)

Option A-3 : PS2 RPS Zippy MRT & MRW series 300W~600W PS2 Mini Redundant power supply (depth at 185mm)

Option A-4 : PS2 RPS SureStar R4B series 600W/700W/800W PS2 Mini Redundant PS (depth at 199mm)

Option A-5 : PS2 RPS Zippy MRG series 500W~800W PS2 Mini Redundant power supply (depth at 200mm)

Option B-1 : NJ-600 600mm 2-layer 3-travel universal rail (cabinet internal depth 600~1200mm compliant)

Option B-2 : NJ-2020-18 18-inch full extension slide rail (cabinet internal depth 456.7mm~810mm compliant)

Option B-3 : 1234U-RMK 1234U rear mounting kit

Option C : D80SM-12 YateLoon 80mmx25mm exhaust fan at small 3pinx500mm (can install 2pcs at rear)

Option D-1 : 25-35-BK 1x5.25" ODD space to 1x3.5" bracket

Option D-2 : 2525T03HDBK 2x5.25" ODD space to 3x3.5" bracket

Option D-3 : 3525T05HDBK 3x5.25" ODD space to 5x3.5" bracket

Option D-4 : N-16TM 1x5.25" to 1x3.5" HotSwap Cage SATA/SAS 12G

Option D-5 : S-16TM 1x5.25" to 1x3.5" HotSwap Cage SATA/SAS 6G

Option D-6 : N-16TL 1x5.25" to 1x3.5" TrayLess HotSwap Cage SATA/SAS 12G

Option D-7 : S-16TL 1x5.25" to 1x3.5" TrayLess HotSwap Cage SATA/SAS 6G

Option D-8 : N-29SS15 1x5.25" to 2x2.5" HotSwap Cage SATA/SAS 12G

Option D-9 : N-67SS 1x5.25" to 6x2.5" HotSwap Cage SATA/SAS 12G

Option D-10 : SS-88TM 1x5.25" to 8x2.5" HotSwap Cage SATA/SAS 6G

Option D-11 : N-49SS-MS 1x5.25" to 4x2.5" HotSwap Cage SFF-8643 12G

Option D-12 : N-49SS 1x5.25" to 4x2.5" HotSwap Cage SATA/SAS 12G

Option D-13 : SS-46TM 1x5.25" to 4x2.5" HotSwap Cage SATA/SAS 6G

Option D-14 : SS-86TM 2x5.25" to 8x2.5" HotSwap Cage SATA/SAS 6G

Option D-15 : N-36TM 2x5.25" to 3x3.5" HotSwap Cage SATA/SAS 12G

Option D-16 : S-36TM 2x5.25" to 3x3.5" HotSwap Cage SATA/SAS 6G

Option D-17 : N-36TL 2x5.25" to 3x3.5" TrayLess HotSwap Cage SATA/SAS 12G

Option D-18 : S-36TL 2x5.25" to 3x3.5" TrayLess HotSwap Cage SATA/SAS 6G

Option D-19 : SS-126TM 3x5.25" to 12x2.5" HotSwap Cage SATA/SAS 6G

Option D-20 : N-46TM-MS 3x5.25" to 4x3.5" HotSwap Cage SFF-8643 12G

Option D-21 : N-46TM 3x5.25" to 4x3.5" HotSwap Cage SATA/SAS 12G

Option D-22 : S-46TM 3x5.25" to 4x3.5" HotSwap Cage SATA/SAS 6G

Option D-23 : N-46TL-MS 3x5.25" to 4x3.5" TrayLess HotSwap Cage SFF-8643 12G

Option D-24 : N-46TL 3x5.25" to 4x3.5" TrayLess HotSwap Cage SATA/SAS 12G

Option D-25 : S-46TL 3x5.25" to 4x3.5" TrayLess HotSwap Cage SATA/SAS 6G

Option D-26 : N-56TM 3x5.25" to 5x3.5" HotSwap Cage SATA/SAS 12G

Option D-27 : S-56TM 3x5.25" to 5x3.5" HotSwap Cage SATA/SAS 6G

Option D-28 : N-56TL 3x5.25" to 5x3.5" TrayLess HotSwap Cage SATA/SAS 12G

Option D-29 : S-56TL 3x5.25" to 5x3.5" TrayLess HotSwap Cage SATA/SAS 6G

Option E-1 : 1MSAS-4SATA-500MM SFF-8087 Mini-SAS (Host) to Four SATA (Device) cable

Option E-2 : SFF-8643-500MM SFF-8643 Mini-SAS HD (Host) to SFF-8643 Mini-SAS HD (Device) cable

Option E-3 : 4SATA-SFF-8643-500MM Four SATA (Host) to SFF-8643 Mini-SAS HD (Device) cable

Option E-4 : SFF-8643-4SATA-500MM SFF-8643 Mini-SAS HD (Host) to Four SATA (Device) cable

Option F-1 : 2U2011A-8080 2U Intel LGA2011 LGA2066 active CPU cooler Square

Option F-2 : 2U2011A-5694 2U Intel LGA2011 active CPU cooler Narrow

Option F-3 : 2U1150A 2U Intel LGA115x Xeon 1230 active CPU cooler

Option F-4 : 2U4094A 2U AMD EPYC SP3 LGA4094 active CPU cooler

Option F-5 : 2U3647A-S82 2U Intel LGA3647 active CPU cooler Square

Option F-6 : 2U3647A-R82-1 2U Intel LGA3647 active CPU cooler Narrow



Latest updated on April 17, 2020